









MULTI-RANGE DIGITAL TIMER 多段式數位型限時繼電器

SPECIFICATION 規格		AH3D-M	AH3D-DM	AH4D-DM	BH3D-DM	
Model 型號						
Dimension(mm) 尺寸		50H*40W*57.5D		48H*48W*84D	48H*48W*53D	
Time Range 時間範圍		x.01Sec, x0.1Sec, x1Sec, x.59Sec x0.1Min, x1Min, x.59Min x0.1Hr, x1Hr, x10Hr				
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz				
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載				
Reset Time 複歸時間		0.1 sec max				
Consumed Power 消耗功率		3VA				
Ambient Temperature 使用周圍溫度		-10°C~+55°C				
Ambient Humidity 使用周圍濕度		45~85%RH				
Life 壽命	Mechanical 機械	5×10 ⁶ times				
	Electrical 電氣	10 ⁵ times				
Weight 重量		130g		150g	136g	
Connection 接線圖		<p>限時2C</p>  <p>mode A</p>		<p>限時1C, 瞬時1C</p>  <p>mode B</p>		
Timing Chart 時序圖		 <p>Rt:Resetting time</p>		 <p>Rt:Resetting time</p>		