









ANALOG TIMER 限時繼電器

SPECIFICATION 規格		AH3-□	CF3-□
Model 型號			
Dimension(mm) 尺寸		50H*40W*57.5D	
Time Range 時間範圍		Sec : 1, 3, 6, 10, 30, 60 Min : 3, 6, 10, 30, 60 Hr : 3, 6, 10, 24	On delay time 0.1S~24H can depend on user requirement
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz	
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載	
Reset Time 複歸時間		0.2 sec max	
Consumed Power 消耗功率		2VA	
Ambient Temperature 使用周圍溫度		-10°C~+55°C	
Ambient Humidity 使用周圍濕度		45~85%RH	
Life 壽命	Mechanical 機械	5×10 ⁶ times	
	Electrical 電氣	10 ⁵ times	
Weight 重量		160g	
Connection 接線圖		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>□-1 限時1C</p>  </div> <div style="text-align: center;"> <p>□-2 限時2C</p>  </div> <div style="text-align: center;"> <p>□-3 限時1C 瞬時1C</p>  </div> </div>	
Timing Chart 時序圖		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>Rt:Resetting time</p> </div> <div style="text-align: center;">  <p>Rt:Resetting time</p> </div> <div style="text-align: center;">  <p>Rt:Resetting time</p> </div> </div>	